



Specifications Ledvance Surface  
Circular 350 White 18W 1440lm - 840  
Cool White | IP44 - Replaces 2x18W

[View Product](#)

General Information

|                          |                                 |
|--------------------------|---------------------------------|
| SKU                      | 243731                          |
| EAN                      | 4058075617964                   |
| Brand                    | Ledvance                        |
| Manufacturer Name        | SF CIRC 350 V 18W 840 IP44 LEDV |
| Any Lamp all-in warranty | 3 Years                         |
| Average Lifetime (h)     | 30000                           |

Technical Information

|                             |                    |
|-----------------------------|--------------------|
| Technology                  | LED Integrated     |
| Wattage                     | 18                 |
| Voltage (V)                 | 220-240            |
| Dimmable                    | Not Dimmable       |
| Colour Code                 | 840 Cool White     |
| Colour temperature (Kelvin) | 4000 Cool White    |
| Colour Rendering (Ra)       | 80-89              |
| Colour of Light             | White              |
| Light colour options        | Single Color       |
| Luminous Flux (Lumen)       | 1440               |
| Luminous Efficacy (lm/W)    | 80                 |
| Optical Cover               | PC (Polycarbonate) |

|              |       |
|--------------|-------|
| Power factor | >0.50 |
|--------------|-------|

|                       |              |
|-----------------------|--------------|
| Product Type Category | LED Bulkhead |
|-----------------------|--------------|

## Fixture Information

|                 |              |
|-----------------|--------------|
| Type of Fixture | Professional |
|-----------------|--------------|

|                 |         |
|-----------------|---------|
| Mounting Method | Surface |
|-----------------|---------|

|                    |                        |
|--------------------|------------------------|
| Fixture Connection | PI [Push-in connector] |
|--------------------|------------------------|

|           |      |
|-----------|------|
| IP-rating | IP44 |
|-----------|------|

|                        |                   |
|------------------------|-------------------|
| Impact Protection (IK) | IK03 - 0.35 joule |
|------------------------|-------------------|

|                       |            |
|-----------------------|------------|
| Operating Temperature | -20 to +40 |
|-----------------------|------------|

|                       |       |
|-----------------------|-------|
| Colour of the Fixture | White |
|-----------------------|-------|

|         |                                |
|---------|--------------------------------|
| Housing | PMMA (Polymethyl Methacrylate) |
|---------|--------------------------------|

|                    |       |
|--------------------|-------|
| Colour of material | White |
|--------------------|-------|

|                    |                   |
|--------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
|--------------------|-------------------|

|        |                      |
|--------|----------------------|
| Series | SURFACE CIRCULAR 350 |
|--------|----------------------|

## Dimensions

|             |     |
|-------------|-----|
| Length (mm) | 350 |
|-------------|-----|

|            |     |
|------------|-----|
| Width (mm) | 350 |
|------------|-----|

## Sensor Information

|                |           |
|----------------|-----------|
| Type of sensor | No Sensor |
|----------------|-----------|

**Why Any-lamp?**



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

