



Specifications Philips LED Waterproof Batten CoreLine WT120C 61W 8000lm - 840 Cool White | 150cm - Interact Dimmable

[View Product](#)

General Information

|                          |                                |
|--------------------------|--------------------------------|
| SKU                      | 249563                         |
| EAN                      | 8719514965348                  |
| Brand                    | Philips                        |
| Manufacturer Name        | WT120C G2 LED80S/840 WIA L1500 |
| Any Lamp all-in warranty | 5 Years                        |
| Average Lifetime (h)     | 50000                          |
| D-Mark                   | Yes                            |

Technical Information

|                             |                                |
|-----------------------------|--------------------------------|
| Technology                  | LED Integrated                 |
| Replaces (Watt)             | 2x58                           |
| Wattage                     | 61                             |
| Voltage (V)                 | 220-240                        |
| Dimmable                    | Dimmable with Philips Interact |
| Colour of Light             | White                          |
| Colour Code                 | 840 Cool White                 |
| Colour temperature (Kelvin) | 4000 Cool White                |
| Colour Rendering (Ra)       | 80-89                          |
| Light colour options        | Single Color                   |
| Luminous Flux (Lumen)       | 8000                           |

|                          |                       |
|--------------------------|-----------------------|
| Luminous Efficacy (lm/W) | 131.1                 |
| Power factor             | >0.90                 |
| Length                   | 150cm                 |
| Product Type Category    | LED Waterproof Batten |

## Fixture Information

|                        |                               |
|------------------------|-------------------------------|
| Mounting Method        | Surface                       |
| Fixture Connection     | PI [Push-in connector 5-pole] |
| Optical Cover          | PC (Polycarbonate)            |
| IP-rating              | IP65                          |
| Impact Protection (IK) | IK08 - 5 joules               |
| Operating Temperature  | -20 to +35                    |
| Housing                | PC (Polycarbonate)            |
| Colour of the Fixture  | Grey                          |
| Colour of material     | Grey                          |
| Emergency Lighting     | No Emergency Unit             |
| Series                 | CoreLine                      |

## Dimensions

|             |      |
|-------------|------|
| Length (mm) | 1515 |
| Width (mm)  | 80   |
| Height (mm) | 85   |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process